

**OUTDOOR MIDI COBRA WALL PACK POWER & CCT SELECTABLE 7/8/10/12W  
910LM to 1560LM 3000K/4000K 130LM/W BLACK RAL9005**

ILWPE005



The Integral LED Cobra Midi Black Wall Pack offers a sophisticated modern look with superior practicality. IP65 weatherproofing and IK10 impact-resistance make it perfect for outdoor applications, whilst the die-cast aluminium body provides a premium finish. Designed for quick and easy installation, the Cobra Midi has options for both side or rear cable entry depending on installation location requirements. This rugged luminaire is ideal for perimeter lighting as well as pedestrian and vehicle access areas in residential, commercial and industrial environments. Providing up to 140lm/W, this luminaire offers selection of 2 CCT options and 4 wattage options.

**Details**

<b>Barcode:</b>	5055788277804
<b>Category:</b>	Luminaires
<b>Range Name:</b>	Cobra
<b>Product Type:</b>	Outdoor
<b>Product Body Finish:</b>	Black
<b>Market Segment:</b>	Outdoor
<b>Finish:</b>	Black
<b>Features:</b>	Hard-wearing and weatherproof
<b>Warranty (Years):</b>	5
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	285
<b>Product Depth (mm):</b>	119
<b>Product Width (mm):</b>	265
<b>Product Weight (g):</b>	4290
<b>Optic:</b>	Polycarbonate diffuser
<b>Material:</b>	ADC12 Aluminium
<b>Construction:</b>	Aluminium
<b>Luminaire Fixing:</b>	Wall
<b>Mounting Type:</b>	Rear Cable Entry
<b>Placement / Application:</b>	Outdoor

**Electrical Data**

	0.95
<b>Power Factor:</b>	220-240
<b>Input Voltage (V):</b>	Non-Dimmable
<b>Dimming:</b>	Yes
<b>Driver Included:</b>	AC
<b>Electric Current:</b>	EN-60598
<b>EN:</b>	Yes
<b>LVD Certified:</b>	

### Light Data

<b>Luminous Flux in Lumens (lm):</b>	1560
<b>Luminous efficacy (lm/W):</b>	123
<b>Correlated Colour Temperature (CCT) (K):</b>	4000
<b>Colour Temperature:</b>	4000K - Cool White
<b>Colour Temperature Name:</b>	Cool White
<b>Beam Angle:</b>	116
<b>Colour Rendering Index (CRI):</b>	80
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Size (mm):</b>	2835
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	50000
<b>Switching Cycles:</b>	100000

### Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>EU Luminaire:</b>	L
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IK Rating (Impact Protection):</b>	IK08
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

### Packaging

<b>Package Weight (g):</b>	4690
<b>Package Length (mm):</b>	335
<b>Package Width (mm):</b>	315
<b>Package Depth (mm):</b>	170