



**DL-PAR38**



**DL-PAR30 DL-PAR20**

- Direct replacement lamps for Mains incandescent Parabolic Aluminium Reflectors Lamps
- Suitable for fire rated fittings
- Aluminium casings
- Aluminium finish with Prismatic Cover
- Standard Size

<b>Incandescent equivalent</b>	<b>30W (mains)</b>	<b>30W (mains)</b>	<b>30W (mains)</b>	<b>30W (mains)</b>	<b>30W (mains)</b>	<b>30W (mains)</b>	<b>30W (mains)</b>
<b>Colour</b>	<b>Daylight</b>	<b>Warm White</b>	<b>Blue</b>	<b>Red</b>	<b>Green</b>	<b>Yellow</b>	<b>Colour Change</b>
<b>Colour Temperature</b>	<b>6000-6500K</b>	<b>3000-3200K</b>	<b>465-475nm</b>	<b>610-630nm</b>	<b>510-530nm</b>	<b>587-593nm</b>	<b>R G B</b>
<b>Input Power</b>	<b>220-240v AC</b>	<b>220-240v AC</b>	<b>220-240v AC</b>	<b>220-240v AC</b>	<b>220-240v AC</b>	<b>220-240v AC</b>	<b>220-240v AC</b>
<b>Lamp Base</b>	<b>ES E27</b>	<b>ES E27</b>	<b>ES E27</b>	<b>ES E27</b>	<b>ES E27</b>	<b>ES E27</b>	<b>ES E27</b>
<b>Dimmable</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>
<b>Lumens</b>	<b>160</b>	<b>135</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>
<b>Wattage (Nominal)</b>	<b>7.8W</b>	<b>7.8W</b>	<b>7.5W</b>	<b>7.5W</b>	<b>7.5W</b>	<b>7.5W</b>	<b>7.8W</b>
<b>Lumens per Watt</b>	<b>21</b>	<b>17</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>
<b>Light View Angles (LVA)</b>	<b>60°</b>	<b>60°</b>	<b>60°</b>	<b>60°</b>	<b>60°</b>	<b>60°</b>	<b>60°</b>
<b>LUX at LVA angles above</b>	<b>165</b>	<b>145</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>
<b>Colour Rendering Index</b>	<b>312</b>	<b>280</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>	<b>N/A</b>
<b>LED Type</b>	<b>DIP</b>	<b>DIP</b>	<b>DIP</b>	<b>DIP</b>	<b>DIP</b>	<b>DIP</b>	<b>DIP</b>
<b>No of LEDs</b>	<b>120</b>	<b>120</b>	<b>120</b>	<b>120</b>	<b>120</b>	<b>120</b>	<b>120</b>
<b>Emergency: Requires</b>	<b>Mains EM Kit</b>	<b>Mains EM Kit</b>	<b>Mains EM Kit</b>	<b>Mains EM Kit</b>	<b>Mains EM Kit</b>	<b>Mains EM Kit</b>	<b>Mains EM Kit</b>
<b>Ingress Protection (IP)</b>	<b>20</b>	<b>20</b>	<b>20</b>	<b>20</b>	<b>20</b>	<b>20</b>	<b>20</b>
<b>Energy Savings per hour</b>	<b>0.2 Pence</b>	<b>0.2 Pence</b>	<b>0.2 Pence</b>	<b>0.2 Pence</b>	<b>0.2 Pence</b>	<b>0.2 Pence</b>	<b>0.2 Pence</b>
<b>Savings per Lamp Life</b>	<b>£111</b>	<b>£111</b>	<b>£113</b>	<b>£113</b>	<b>£113</b>	<b>£113</b>	<b>£111</b>

Lamp-Life is affected by surrounding levels of Heat, Ventilation, Humidity and Air Particles  
 Avoid placing lamps in fixtures a) Without facilities for heat dissipation b) Where internal condensation is present c) Powered by Electronic Low Voltage Halogen Transformer