



- Surface Mount (Wall)
- White Polycarbonate Body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP40 rated
- 30m Viewing Distance
- ISO Legends as Standard
- DDP (Deep Discharge Protection)
- Samsung LED's
- Supplied With a Kit of Legends

A stylish and compact wall mounting Single Sided LED Exit Sign that can either be surface or semi-recesses mounted. The unit is available in either a Switchable Maintained/Non-Maintained or a DALI Self-Test version. The unit comes with a Plexi glass screen printed legend plate which offers an impressive 30m viewing distance. The legend panels supplied with the product are Arrow Down (AD), Arrow Left (AL) and Arrow Right (AR). Arrow Up (AU) is available as an accessory. The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

| | |
|------------|--|
| CE2S/2W/M3 | Switchable Maintained |
| CE2S/2W/DA | DALI Self-Test Maintained via Mains Switch |

Technical Details:

| | CE2S/2W/M3 | CE2S/2W/DA |
|---------------------------|---|--------------------------|
| Mains Supply | 230-240V AC 50/60 Hz | |
| Power Rating Maintained | 55mA $\lambda = 0.6$ | 40mA $\lambda = 0.6$ |
| Duration | 3 Hours | |
| Recharge Period | 12 Hours – Energy saving electronic charger | |
| Battery Size & Type | 6.4V 3.0Ah LiFePO4 Cells | 9.6V 1.5Ah LiFePO4 Cells |
| Charge Current | 0-400mA Dual Rate Charge | 0-150mA Dual Rate Charge |
| Ingress Protection Rating | IP40 | |
| Class | Class II | |
| Weight | 1.42Kg | 1.43Kg |