



product details

64684 ECO

Product description: 64684 ECO
Product code: 4008321928054
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321928054

Applications	
Dimmable	Yes
Burning position	any
Fuse, quick-acting	2.0 A

Categorizations	
SEG number	8327676
ILCOS	HDG-48-230-R7s-74,9

Certificates & Standards	
EEL - Energy Label	C

General Description	
Base (standard designation)	R7s
Mercury-free	Yes
Rated lamp mercury content	0.0 mg
New article	NEW

Technical - Electrical Data	
Nominal wattage (packaging)	48 W
Construction wattage	48 W
Claimed equivalent incand. lamp power	60 W
Nominal voltage	230 V
Rated number of switching cycles	1000000
Rated power factor λ	1.00

Technical - Geometries	
Overall length	74.90 mm
Contact spacing	74.9 mm
Diameter	12.00 mm
Length	74.90 mm

Technical - Lifespan	
Nominal lamp life time	1000 h
Rated lamp life time	1000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	100
Luminous flux	815 lm
Nominal luminous flux	750 lm
Rated luminous flux	750 lm
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2900 K



12.04.2011

Subject to change without notice. Errors and omission excepted.
© 2011 OSRAM GmbH

Page 1 of 2



product details

64684 ECO

Technical - Light Technical Data	
Rated color temperature	2900 K
Color rendering index Ra	100
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321928054	Folding carton box contains 1 Piece	21.000 mm x 18.000 mm x 87.000 mm	6.000 g (0.000 g)	0.033 Cubic dec.
4008321945082	Shipping carton box contains 20 Piece	113.000 mm x 77.000 mm x 94.000 mm	197.000 g (0.000 g)	0.818 Cubic dec.

HALOLINE ECO from OSRAM is the classic lamp for small outdoor systems for floodlighting buildings and sports arenas and for security lighting. It is also experiencing a renaissance in the home. In addition to providing indirect lighting, innovative pendant luminaires are re-conquering classic applications, providing wide-area lighting in a wide range of new and exciting designs.

- Brilliant ECO accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO₂ emissions
- Lower thermal output (compared with the standard reference product)
- Ideal for emphasizing and accentuating the structure of a room
- No transformer required
- Average life: 2,000 h
- Dimmable
- R_a=100
- Color temperature: 48 W/80 W/120 W short - 2,900 K; 120 W long/160 W/230 W/400 W - 2,950 K
- Design: 74.9 mm (48 W, 80 W 120 W short); 114.2 mm (120 W long, 160 W, 230 W, 400 W)
- Base: R7s