



product details

64690 ECO

Product description: 64690 ECO
 Product code: 4008321928078
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321928078

| Applications | |
|--------------------|-------|
| Dimmable | Yes |
| Burning position | any |
| Fuse, quick-acting | 2.0 A |

| Categorizations | |
|-----------------|---------------------|
| SEG number | 8327678 |
| ILCOS | HDG-80-230-R7s-74,9 |

| Certificates & Standards | |
|--------------------------|---|
| EEL - Energy Label | C |

| General Description | |
|-----------------------------|--------|
| Base (standard designation) | R7s |
| Mercury-free | Yes |
| Rated lamp mercury content | 0.0 mg |

| Technical - Electrical Data | |
|---------------------------------------|---------|
| Nominal wattage (packaging) | 80 W |
| Construction wattage | 80 W |
| Claimed equivalent incand. lamp power | 100 W |
| Nominal voltage | 230 V |
| Rated number of switching cycles | 1000000 |
| Rated power factor λ | 1.00 |

| Technical - Geometries | |
|------------------------|----------|
| Overall length | 74.90 mm |
| Contact spacing | 74.9 mm |
| Diameter | 12.00 mm |
| Length | 80.30 mm |

| Technical - Lifespan | |
|------------------------|--------|
| Nominal lamp life time | 2000 h |
| Rated lamp life time | 2000 h |

| Technical - Light Technical Data | |
|---|---------|
| Rated color rendering index (Ra) | 100 |
| Luminous flux | 1450 lm |
| Nominal luminous flux | 1400 lm |
| Rated luminous flux | 1400 lm |
| Lumen main.fact.at end of nom.life time | 0.80 |
| Color temperature | 2900 K |
| Rated color temperature | 2950 K |





product details

64690 ECO

| Technical - Light Technical Data | |
|----------------------------------|-------|
| Color rendering index Ra | 100 |
| Rated warm-up time (60 %) | 0 s |
| Rated starting time | 0.0 s |

| Packaging units | | | | |
|-----------------|---------------------------------------|------------------------------------|---------------------|------------------|
| Product code | Packaging type and content | Dimensions in h x w x l | Gross weight | Volume |
| 4008321928078 | Folding carton box contains 1 Piece | 21.000 mm x 20.000 mm x 87.000 mm | 8.500 g (0.000 g) | 0.040 Cubic dec. |
| 4008321327758 | Shipping carton box contains 20 Piece | 92.000 mm x 77.000 mm x 112.000 mm | 207.000 g (0.000 g) | 0.877 Cubic dec. |

HALOLINE ECO from OSRAM is the classic lamp for small outdoor systems for floodlighting buildings and sports arenas and for security lighting. It is also experiencing a renaissance in the home. In addition to providing indirect lighting, innovative pendant luminaires are re-conquering classic applications, providing wide-area lighting in a wide range of new and exciting designs.

- Brilliant ECO accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO2 emissions
- Lower thermal output (compared with the standard reference product)
- Ideal for emphasizing and accentuating the structure of a room
- No transformer required
- Average life: 2,000 h
- Dimmable
- $R_a=100$
- Color temperature: 48 W/80 W/120 W short - 2,900 K; 120 W long/160 W/230 W/400 W - 2,950 K
- Design: 74.9 mm (48 W, 80 W 120 W short); 114.2 mm (120 W long, 160 W, 230 W, 400 W)
- Base: R7s