



product details

**41930 SP**

Product description: 41930 SP  
Product code: 4050300003979  
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:  
[http://catalog.myosram.com?~language=EN&~country=COM&it\\_p=4050300003979](http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300003979)

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
ILCOS	HMG//UB-20-24-GY4-48/8

General Description	
Base (standard designation)	GY4
Mercury-free	Yes

Technical - Electrical Data	
Nominal wattage (packaging)	20 W
Construction wattage	20 W
Nominal voltage	24 V

Technical - Geometries	
Overall length	36.00 mm
Contact spacing	4 mm
Diameter	48.0 mm
Length	38.00 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Luminous intensity	3100 cd
Beam angle	8 °
Color temperature	2900 K
Color rendering index Ra	100
Rated starting time	0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300003979	Folding carton box contains 1 Piece	44.000 mm x 44.000 mm x 57.000 mm	30.000 g (0.000 g)	0.110 Cubic dec.
4050300225418	Shipping carton box contains 10 Piece	96.000 mm x 69.000 mm x 231.000 mm	261.000 g (0.000 g)	1.530 Cubic dec.



product details

## 41930 SP

**Presenting things in a better light. Thanks to their excellent spotlighting and extremely high luminous intensity HALOSPOT 48 from OSRAM are real professionals when it comes to presenting rooms and objects in their best light. The faceted reflector ensures the light is evenly distributed. With HALOSPOT lamps there is no need to worry about heat building up in suspended ceilings because the aluminum reflector ensures that most of the heat is emitted forwards.**

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Excellent distribution of light thanks to faceted reflector
- Drastically reduced thermal load in the luminaire thanks to an aluminium-coated reflector which emits most of the heat forwards
- Approved for use in open luminaires to IEC 60598-1
- Average life: AR48 20 W 24 V - 1,000 h; AR48 20 W 12 V - 2,000 h
- Dimmable\*
- Ra=100
- Color temperature: 2,800 K
- Base: BA15d, GY4
- UV filter

For light distribution curves go to [www.osram.com](http://www.osram.com)

\*A buzzing tone may be heard when dimmed using certain dimmers. Recommendation: OSRAM HTI DALI 150/230-240 DIM with OSRAM DALI MCU