



product details

QTIS e 2x58/220-240



Product description: QTIS e 2x58/220-240
Product code: 4050300940618
Quantity: Unpacked (UNV) contains 1 Piece (PCE)

Applications	
Suitable f. fixtures with prot. class	class I
Dimmable	No

Certificates & Standards	
Approval marks - approval	VDE
EEL - Energy Label	A3
Standards	acc. to EN 61347-2-3 acc. to EN 55015:2006 + A1:2007 acc. to EN 61000-3-2 acc. to EN 61547
Type of protection	IP20

General Description	
Design / version	ECG standard

Logistical Data	
Product weight	317.160 g
Relative humidity	5...85 % ¹⁾
Temperature range at storage	-40...85 °C

Technical - Electrical Data	
Inrush current	48 A
Nominal voltage	220-240 V
Mains frequency	50-60 Hz
DC voltage	198...264 V ²⁾
Operating frequency	45...50 kHz
Max. no. of ECGs on circuit breaker 10 A	5
Max. no. of ECGs on circuit breaker 16 A	8
TH full width at half maximum	260 µs

Technical - Geometries	
Length	360.00 mm
Width	30.00 mm
Height	30.00 mm
Mounting hole spacing, length	350 mm

Technical - Temperatures	
Ambient temperature range	-15...+50 °C
Operating temperature	70 °C
Max. housing temperature in case of fault	110 °C

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300940618	Unpacked contains 1 Piece	38,000 mm x 31,000 mm x 346,000 mm	317,160 g (0,000 g)	0,513 Cubic dec.





product details

QTIS e 2x58/220-240

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300663814	Shipping carton box contains 20 Piece	167,000 mm x 130,000 mm x 391,000 mm	6.589,200 g (0,000 g)	8,489 Cubic dec.

General

- Supply voltage: 220 - 240 V
- Line frequency: 50 - 60 Hz
- Line voltage: 198 - 254 V
- Not suitable for DC operation
- Instant start within 0.3 s
- Automatic safety shutdown of lamps in the event of a defect or at end of life
- Automatic restart of replacement lamps
- Energy Efficiency Index EEI=A3
- Approval marks: EMV Sign
- Safety: to EN 61347-2-3
- RI suppression: to EN 55015:2006+A1:2007/CISPR 15
- Line harmonics: to EN 61000-3-2
- Immunity: to EN 61547

1) Maximum 56 days/year at 85 %

2) Without approbation



Wiring diagram:

QTISe 2x18/220-240

