




## AGLX020SS

1W IP67 316L Stainless Steel Finish  
Baffle Honeycomb Ground Light

### PRODUCT FEATURES

- IP67 316L Stainless Steel Finish
- Glare-Reducing Honeycomb
- Drive Over Rated (2 Metric Tonnes)\*
- Toughened Flush Glass
- 2 Metre Pre-Wired Tough Rubber Robust Cable For Extreme Outdoor Use
- 350mA Constant Current (Series Wiring)
- 15° Narrow Beam Angle
- Robust Metal Cable Gland



Cutout:  
Ø20 mm  
Overall Diameter:  
Ø27 mm  
Overall Depth:  
32 mm

### TECHNICAL SPECIFICATIONS

Product Code	AGLX020SS/27	AGLX020SS/30	AGLX020SS/40
Luminous Flux (LM)	76LM	77LM	81LM
Useful Luminous Flux (LM)	76LM	77LM	81LM
CCT (Kelvin)	2700K	3000K	4000K
Beam Angle (°)	15°	15°	15°
SDCM	<6	<6	<6
CRI	>80	>80	>80
Peak Intensity	376cd	408cd	393cd
Operating Voltage (V)	3V	3V	3V
Max Output Power (W)	1W	1W	1W
Operating Current (A max)	350mA**	350mA**	350mA**
Class	III	III	III
Cut Out	20mm	20mm	20mm
Frame Colour	Stainless Steel	Stainless Steel	Stainless Steel
Switching Cycles	<100,000	<100,000	<100,000
Ingress Protection	IP67	IP67	IP67
Ambient Operating Temperature (°C)	-20°C ~ +50°C	-20°C ~ +50°C	-20°C ~ +50°C
Guarantee	3 years	3 years	3 years
Dimmable	Yes*	Yes*	Yes*
Life Time (L70 B50)	50,000h	50,000h	50,000h



\*When installed with Mounting Sleeve (included)  
\*\*When used with a suitable ALL LED dimmable driver  
\*\*350mA driver required (sold separately)




## AGLX020WH

1W IP67 Polar White Finish  
Baffle Honeycomb Ground Light

### PRODUCT FEATURES

- IP67 Polar White Finish
- Glare-Reducing Honeycomb
- Drive Over Rated (2 Metric Tonnes)\*
- Toughened Flush Glass
- 2 Metre Pre-Wired Tough Rubber Robust Cable For Extreme Outdoor Use
- 350mA Constant Current (Series Wiring)
- 15° Narrow Beam Angle
- Robust Metal Cable Gland



Cutout:  
Ø20 mm  
Overall Diameter:  
Ø27 mm  
Overall Depth:  
32 mm

### TECHNICAL SPECIFICATIONS

Product Code	AGLX020WH/27	AGLX020WH/30	AGLX020WH/40
Luminous Flux (LM)	76LM	77LM	81LM
Useful Luminous Flux (LM)	76LM	77LM	81LM
CCT (Kelvin)	2700K	3000K	4000K
Beam Angle (°)	15°	15°	15°
SDCM	<6	<6	<6
CRI	>80	>80	>80
Peak Intensity	376cd	408cd	393cd
Operating Voltage (V)	3V	3V	3V
Max Output Power (W)	1W	1W	1W
Operating Current (A max)	350mA**	350mA**	350mA**
Class	III	III	III
Body Material	Aluminium	Aluminium	Aluminium
Cut Out	20mm	20mm	20mm
Frame Colour	Texture White	Texture White	Texture White
Switching Cycles	<100,000	<100,000	<100,000
Ingress Protection	IP67	IP67	IP67
Ambient Operating Temperature (°C)	-20°C ~ +50°C	-20°C ~ +50°C	-20°C ~ +50°C
Guarantee	3 years	3 years	3 years
Dimmable	Yes*	Yes*	Yes*
Life Time (L70 B50)	50,000h	50,000h	50,000h



\*When installed with Mounting Sleeve (included)  
\*\*When used with a suitable ALL LED dimmable driver  
\*\*350mA driver required (sold separately)