


Data Specification Sheet



SIZE	A	B
18W	617	41.7
36W	1227	60.0
58W	1527	60.0
70W	1791	60.0



T8 Batten Fluorescent Fittings

Code	T8118HF	T8136HF T8136EMHF	T8158HF T8158EMHF	T8170HF T8170EMHF	T8218HF T8136EMHF	T8236HF	T8258HF	T8270HF
Wattage	18W	36W	58W	70W	2x18W	2x36W	2x58W	2x70W
Description	High Frequency Fluorescent T8 Battens							
Finishes available	White							
Overall dimensions	See above diagram							
Fixing Centres	See above diagram							
Typical location	Indoor							
Accessories available	Reflectors (Powder coated white mild steel) T8136HF-T8170HF, T8236HF-T8270HF Prismatic Diffusers T8136HF-T8170HF, T8236HF-T8270HF							
Lamp Supplied	No							
Voltage (V)	220-230V 50Hz							
Class	Class I. Must be Earthed							
IP	IP20							
Photometric Testing	Yes							
Instruction sheet	Yes							
Origin of manufacture	China							
Main materials:								
Body	Powder Coated Mild Steel							
Method of fix	Direct to ceiling or chain							
Lamp holder cap	G5							
Lamp type	T8							
Electrical Connections	10A L.E.N. Nylon Connector, Screw Terminals							
Running Gear / Make / Operating Temperature	Soft Start H.F. Electronic ballast Soft Start H.F. Electronic ballast c/w integral Inverter & Battery Pack - 20°C to +30°C							
Dimmable	No							
Cold Store Version - 20°C	No							
CE mark	Yes							
Quality Assurance System	Yes ISO 9001 QMS							
Batch coding details	Yes							
Certificate of Conformity	Yes							
Manufactured in accordance	EN60 598-2-1							
Guarantee Period	1 Year							