

### Cleaning:

- > Clean this light fitting only with a soft dry cloth
- > Do not use any chemical or abrasive cleaners.

### Lamp replacement:

- > Switch off the electricity at the mains.
- > Unscrew the end of the fitting and remove the ring complete with the glass ( see diagram inside ).
- > Twist the lamp anticlockwise and withdraw.
- > Replace lamp.
- > Re-fit end of fitting taking great care not to damage the silicone gaskets.
- > Restore the power and switch on.

### Replacement lamp type:

Wattage: 35 W  
Supply Voltage: 240 V  
Type: GU10

### Eventually, you may want to replace this light fitting:

When your light fitting comes to the end of its life or you choose to update or upgrade it by replacing it, please do not dispose of it with your normal household waste, please recycle where facilities exist. When you need to dispose of this fitting, check with your retailer or local authority for suitable options. New regulations will encourage the recycling of Waste from Electrical and Electronic Equipment ( European "WEEE Directive" effective August 2005 ).



### If you experience problems:

If your light is defective or develops a fault, please return it to the place where you bought it. You can call our Helpline for advice. The Helpline will gladly give advice on any aspect of any Eterna Lighting product but may not be able to give specific instructions regarding individual installations. If in doubt, consult a qualified electrician.

### Help line:

Tel: 01933 673 144 Fax: 01933 678 083 Email: [sales@eterna-lighting.co.uk](mailto:sales@eterna-lighting.co.uk)  
For answers to frequently asked questions ( FAQs ) and other information visit our web-site  
[www.eterna-lighting.co.uk](http://www.eterna-lighting.co.uk)



# IMPORTANT!

## Safety and Installation instructions

## Adjustable Stainless Steel Wall Light

**Model(s)**  
WG-903D

### Pack contents:

Stainless Steel Wall fitting	1
Black wall mounting plate	1
Hexagonal domed nuts and washers	2

**PLEASE READ THESE INSTRUCTIONS BEFORE  
INSTALLING YOUR NEW FITTING**

**PLEASE RETAIN FOR FUTURE REFERENCE**

## Read this first:

- > This light fitting must be installed in accordance with the Building Regulations. These may be obtained from HMSO or viewed and downloaded from [www.gov.uk](http://www.gov.uk) following the link for Building Regulations.
- > If in any doubt, consult a qualified electrician.
- > Switch off the mains before commencing installation and remove the appropriate circuit fuse.
- > Suitable for indoor or outdoor use.
- > This product is suitable for installation on surfaces with normal flammability ( indicated by the "F" in a triangle ) e.g. wood, plasterboard, masonry. It is not suitable for use on highly flammable surfaces ( e.g. polystyrene, textiles ).
- > Before making fixing hole(s), check that there are no obstructions hidden beneath the mounting surface such as pipes or cables.
- > The chosen location of your new fitting should allow for the product to be securely mounted and safely connected to the mains supply ( lighting circuit ).
- > The lamp must be positioned so that there is at least 0.5m ( 500mm ) between the bulb and any illuminated surface. Spotlights should be positioned well away from curtains and beds to ensure this distance is maintained.
- > If the location of your new fitting requires the provision of a new electrical supply, the supply must conform with the requirements of the Building Regulations.
- > This product is designed for permanent connection to fixed wiring: this should be either a suitable lighting circuit ( protected with a 5 or 6 Amp MCB or fuse ) or a fused spur ( with a 3 Amp fuse ) via a fused connection unit. We recommend that the supply incorporates a switch for ease of operation.
- > Make connections to the electrical supply in accordance with the following code:
  - Live - Brown or Red
  - Neutral - Blue or Black
  - Earth - Green and Yellow
- > This product must be connected to Earth.
- > IMPORTANT— Always switch off at the mains before changing the lamp.
- > You are advised at every stage of your installation to double-check any electrical connections you have made. After you have completed your installation there are electrical tests that should be carried out: these tests are specified in the Wiring Regulations ( BS7671 ) referred to in the Building Regulations. If in doubt, consult a qualified electrician.

## Installation:

- 1) Choose the location for your light fitting giving consideration to the points above.
- 2) Remove the two hexagonal nuts and the washers from the front of the fitting and lift out the black wall bracket from the back.
- 3) Lift the terminal block off the black wall bracket.
- 4) Using the black wall bracket as a template, mark the location of the fixing holes on your mounting surface.
- 5) Make the fixing holes as appropriate to your mounting surface and fixings.

Safety markings:



- 6) Pierce the rubber grommet in the back of the wall bracket just enough for the cable to pass through and so that the grommet remains tight around the cable.
- 7) Thread the cable through the grommet.
- 8) Secure the wall bracket to the wall.
- 9) Make the electrical connections according to the colour code opposite.
- 10) Press the terminal block into place inside the black wall bracket.
- 11) Check that the rubber gasket is correctly positioned around the wall bracket and offer the fitting up to the bracket locating the two protruding screws in the holes in the front of the fitting.
- 12) Position the two washers over the screws and secure the fitting in place using the two hexagonal nuts.
- 13) Fit a new lamp following the instructions on the back page of these instructions and observing the maximum Wattage and lamp type.
- 14) Adjust the head to the desired operational position.
- 15) Restore the power and switch on.

**IMPORTANT:** Do not adjust the head position with bare hands if the light has been switched on as the body of the fitting will be hot.

