

**OUTDOOR NANO COBRA WALL PACK 5W 635LM CCT SELECTABLE
3000K/4000K 127LM/W ANTHRACITE RAL7016**

ILWPE002



The Integral LED Cobra Nano Anthracite Wall Pack offers a sophisticated modern look with superior practicality. IP65 weatherproofing and IK10 impact-resistance make it perfect for outdoor applications, whilst the die-cast aluminium body provides a premium finish. Designed for quick and easy installation, this rugged luminaire is ideal for perimeter lighting as well as pedestrian and vehicle access areas in residential, commercial and industrial environments. Providing 120lm/W, this small yet efficient luminaire offers 3000K/4000K CCT selection.

Details

Barcode:	5055788277774
Category:	Luminaires
Range Name:	Cobra
Product Type:	Outdoor
Product Body Finish:	Anthracite
Market Segment:	Outdoor
Finish:	Anthracite
Features:	Hard-wearing and weatherproof
Warranty (Years):	5
CE RoHS:	Yes

Physical Data

Product Length (mm):	241.7
Product Depth (mm):	76
Product Width (mm):	150
Product Weight (g):	1170
Optic:	Polycarbonate diffuser
Material:	ADC12 Aluminium
Construction:	Aluminium
Luminaire Fixing:	Wall
Mounting Type:	Rear Cable Entry
Placement / Application:	Outdoor

Electrical Data

Power Factor:	0.95
----------------------	------

Input Voltage (V):	220-240
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	635
Luminous efficacy (lm/W):	105
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature:	4000K - Cool White
Colour Temperature Name:	Cool White
Beam Angle:	115
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	50000
Switching Cycles:	100000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
EU Luminaire:	L
Hg 0% (Mercury Free):	Yes
IK Rating (Impact Protection):	IK08
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	1370
Package Length (mm):	255
Package Width (mm):	160
Package Depth (mm):	100