EVOFIRE FIRE RATED DOWNLIGHT 70MM CUTOUT IP65 ANTIQUE BRASS ROUND +GU10 HOLDER INTEGRAL

ILDLFR70D045



The Evofire Fire Rated Downlight is a safe and attractive fitting for a GU10 or MR16 LED lamp. The fully open design of the Evofire does not conceal your lamp in a large metal canister, which can trap some of the heat it generates, lowering lamp lifetime and performance. Lamps installed in an Evofire run at up to 10 degrees C cooler than a typical can-style fire rated downlight from leading LED brands - this can extend the lifetime of your lamps. As well being very tough thanks to its steel construction, The Evofire is also a highly aesthetic choice for Fire Rated lighting. The 1mm blend-in bezel is up to 10 times thinner than typical IP65 rated downlights, has a high quality powder coating and fits almost flush with your ceiling, so the downlight looks discreet and pleasing in any setting. This downlight is fire rated to 30, 60 and 90 minutes in compliance with BS476 Part 21:1987, Air Tightness compliant with Part C and Part L and Resistance to Sound compliant with Part E. See installation guide for full details. Evofire shown with Real Colour GU10 LED lamp (sold separately).

Perfect for installing downlights in low-profile areas.



Example: Use ILDLFR70D001 + ILMDC001 to achieve a profile as low as 38.5mm

Evolight fitted in a downlight

Details

Quick Order Code: Barcode: Category: Range Name: Product Type: Product Body Finish: Market Segment: Finish: Features: Fixed/Tiltable: Warranty (Years): CE RoHS:

692626 5055788268123 Downlights Evofire Fire Rated Antique Brass Commercial indoor, Residential indoor Antique Brass Without Insulation Guard Fixed 3 Yes

Physical Data

Product Depth (mm):	39
Product Weight (g):	138
Material:	Steel, Glass
Overall diameter (mm):	85
Construction:	Pressed Steel, Glass
Cut Out Diameter (mm):	70
Bulb or Luminaire Shape:	Round
Luminaire Fixing:	Recess mounted
Placement / Application:	Indoor, General Lighting
Electrical Data	
Insulation Guard:	No
Light Data	
Fire Rating (mins):	30, 60, 90
Environment	
CE RoHS:	Yes
IP Rating (Back/Recessed side):	IP20
IP Rating (Ingress Protection):	IP65
Packaging	
Package Weight (g):	153
Package Length (mm):	90
Package Width (mm):	90
Package Depth (mm):	65
Qty per euro pallet:	3400

Portal.integral-led.com