

# OMNI FILAMENT GLS BULB B22 1521LM 11.2W 4000K DIMMABLE 320 BEAM CLEAR FULL GLASS INTEGRAL

ILGLSB22DE141



Integral Filament Omni GLS Lamps utilise Filament LED technology to create a decorative look and wide beam angle that looks fantastic in ceiling pendants and fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

#### **Details**

Quick Order Code: 331395

**Barcode**: 5055788272014

Category:LampsRange Name:OmniProduct Type:GLS

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

### **Physical Data**

Product Length (mm): 103
Product Width (mm): 60
Product Weight (g): 33

Material:Aluminium, GlassBase Term:Bayonet cap

Bulb Base: B22

**Construction:** Glass shell, Filament strip, Aluminium base

Globe Finish:ClearGlobe Type:GLSBulb or Luminaire Shape:Round

Placement / Application: Indoor, General Lighting

#### **Electrical Data**

Power (W): 11.2
Power Consumption (W): 11.2
Power Factor: 0.7
Wattage equivalent (W): 100
Amperage (mA): 47

**Dimming:** Dimmable with compatible dimmers

Driver Included: Yes
Electric Current: AC

**EN:** EN-62560

LVD Certified: Yes

## **Light Data**

Luminous Flux in Lumens (Im): 1521 Luminous efficacy (Im/W): 136 Correlated Colour Temperature (CCT) (K): 4000

Colour Temperature: 4000K - Cool White

Colour Temperature Name: Cool White

Beam Angle: 320
Colour Rendering Index (CRI): 80

Compatible Dimmers: Varilight JQP401W

Frequency Range (Hz): 50/60
Instant on (Less than 1 second): Yes


**LED Type:** Filament chip


Lifetime (hours): 15000 Switching Cycles: 7500

#### **Environment**

**EN:** EN-62560

LVD Certified: Yes **CE RoHS:** Yes **Previous Energy Rating:** A++ D **New Energy Rating:** Hg 0% (Mercury Free): Yes **IP Rating (Ingress Protection):** IP20 **Lowest Operating Temperature (°C):** -20 **Maximum Operating Temperature (°C):** 40





# **Packaging**

Portal.integral-led.com

Package Length (mm):120Package Width (mm):65Package Depth (mm):65Qty per euro pallet:1440