

OMNI FILAMENT GLS BULB B22 1521LM 11.2W 2700K DIMMABLE 320 BEAM CLEAR INTEGRAL

ILGLSB22DC123



Integral Filament Omni GLS Lamps utilise Filament LED technology to create a decorative look and wide beam angle that looks fantastic in ceiling pendants and fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

Details

Quick Order Code: 589394

Barcode: 5055788260226

Category: Lamps
Range Name: Omni

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

Physical Data

Product Length (mm): 103
Product Width (mm): 60
Product Weight (g): 33

Material:Aluminium, GlassBase Term:Bayonet cap

Bulb Base: B22

Construction: Glass shell, Filament strip, Aluminium base

Globe Finish: Clear
Globe Type: GLS
Bulb or Luminaire Shape: Round

Placement / Application: Indoor, General Lighting

Spot Type: Filament

Electrical Data

Power (W):	11.2
Power Consumption (W):	11.2
Power Factor:	0.7
Wattage equivalent (W):	100
Amperage (mA):	47

Dimming: Dimmable with compatible dimmers

Driver Included:YesElectric Current:ACTrue Wattage Eq (W):100

EN: EN-62560

LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 1521
Luminous efficacy (Im/W): 136
Correlated Colour Temperature (CCT) (K): 2700

Colour Temperature: 2700K - Warm

Colour Temperature Name:WarmBeam Angle:320Colour Rendering Index (CRI):80Colour Type:SingleFrequency Range (Hz):50/60Instant on (Less than 1 second):Yes


LED Type: Filament chip


Lifetime (hours): 15000 Switching Cycles: 7500

Environment

EN: EN-62560

LVD Certified: Yes **CE RoHS:** Yes A++ **Previous Energy Rating: New Energy Rating:** D Hg 0% (Mercury Free): Yes IP20 **IP Rating (Ingress Protection):** Lowest Operating Temperature (°C): -20 **Maximum Operating Temperature (°C):** 40





Packaging

Portal.integral-led.com

Package Weight (g): 120
Package Length (mm): 65
Package Width (mm): 65
Package Depth (mm):