

**OUTDOOR MEDIUM COBRA WALL PACK 3HR EMERGENCY POWER & CCT
SELECTABLE 7/8/10/12W 910LM to 1560LM 3000K/4000K 130LM/W
ANTHRACITE RAL7016**

ILWPE006



The Integral LED Cobra Midi Anthracite Wall Pack offers a sophisticated modern look with superior practicality. IP65 weatherproofing and IK10 impact-resistance make it perfect for outdoor applications, whilst the die-cast aluminium body provides a premium finish. Designed for quick and easy installation, the Cobra Midi has options for both side or rear cable entry depending on installation location requirements. This rugged luminaire is ideal for perimeter lighting as well as pedestrian and vehicle access areas in residential, commercial and industrial environments. Providing up to 140lm/W, this luminaire offers selection of 2 CCT options and 4 wattage options. Complete with an inbuilt emergency lighting pack, the Cobra meets the standards set by UK regulation BS EN 1838.

Details

Barcode:	5055788277811
Category:	Luminaires
Range Name:	Cobra
Product Type:	Outdoor
Product Body Finish:	Anthracite
Market Segment:	Outdoor
Finish:	Anthracite
Features:	Hard-wearing and weatherproof
Warranty (Years):	5
CE RoHS:	Yes

Physical Data

Product Length (mm):	285
Product Depth (mm):	119
Product Width (mm):	265
Product Weight (g):	4290
Optic:	Polycarbonate diffuser
Material:	ADC12 Aluminium
Construction:	Aluminium
Luminaire Fixing:	Wall
Mounting Type:	Rear Cable Entry
Placement / Application:	Outdoor

Electrical Data

Power Factor:	0.95
Input Voltage (V):	220-240
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	1560
Luminous efficacy (lm/W):	123
Correlated Colour Temperature (CCT) (K):	4000
Colour Temperature:	4000K - Cool White
Colour Temperature Name:	Cool White
Beam Angle:	116
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	50000
Switching Cycles:	100000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
EU Luminaire:	L
Hg 0% (Mercury Free):	Yes
IK Rating (Impact Protection):	IK08
IP Rating (Ingress Protection):	IP65
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	4690
Package Length (mm):	335
Package Width (mm):	315
Package Depth (mm):	170