

**PAR38 BULB E27 15W BLUE NON-DIMM IP65 INTEGRAL**

ILPAR38NJ010



Integral LED IP65-rated PAR lamps have been designed for use in outdoor areas such as gardens, country parks, and estates where you can illuminate flowerbeds, trees, statues and walls for example, creating beautiful feature points. The lamps are available in a selection of colours, as well as a high CRI warm white. Please note: This IP65 PAR38 is only for use in suitably rated outdoor fittings and sockets.

**Details**

<b>Quick Order Code:</b>	'023000
<b>Barcode:</b>	5055788227311
<b>Category:</b>	Lamps
<b>Range Name:</b>	Outdoor
<b>Product Type:</b>	PAR
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial and Residential outdoor
<b>Warranty (Years):</b>	2
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	128
<b>Product Weight (g):</b>	230
<b>Optic:</b>	Refractor Cover for enhanced light distribution
<b>Material:</b>	Aluminium, Polycarbonate
<b>Base Term:</b>	Edison screw
<b>Bulb Base:</b>	E27
<b>Construction:</b>	Plastic and Aluminium heat-sink, PMMA diffuser
<b>Globe Finish:</b>	Clear
<b>Globe Type:</b>	PAR38
<b>Bulb Fixing:</b>	Downlight, Spotlight
<b>Placement / Application:</b>	Outdoor, General Lighting
<b>Spot Type:</b>	COB

**Electrical Data**

<b>Power (W):</b>	15
<b>Power Consumption (W) :</b>	15
<b>Power Factor:</b>	0.9

<b>Wattage equivalent (W):</b>	135
<b>Amperage (mA):</b>	67
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes

## Light Data

<b>Colour Temperature:</b>	Blue
<b>Colour Temperature Name:</b>	Blue
<b>Beam Angle:</b>	36
<b>Colour Type:</b>	Single
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Chip-on-board (COB)
<b>Lifetime (hours):</b>	25000
<b>Switching Cycles:</b>	12500

## Environment

<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP65
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging

<b>Package Weight (g):</b>	320
<b>Package Length (mm):</b>	125
<b>Package Width (mm):</b>	125
<b>Package Depth (mm):</b>	145