

SUNSET GLOBE G125 B22 170LM 2.5W 1800K NON-DIMM 300 BEAM AMBER INTEGRAL

ILGLOBB22N006



Create a relaxing ambience with an ultra-warm (1800K), energy-saving LED filament lamp. The Sunset range has a retro look with tinted amber glass and an eye-catching vintage design.

Built using the latest LED filament technology to deliver an A+ energy rating and 93% energy savings compared to the incandescent lamp it replaces. Enjoy the classic aesthetic look but with an improved lifetime of 15,000 hours.

The wattage comparison is made between the Sunset LED Globe and its equivalent vintage incandescent decorative lamp. This offers a more accurate representation of the product's luminous efficacy. The ErP equivalent for reference is 2.5w (170lm) = 18W.

Details

Quick Order Code:	436358
Barcode:	5055788218449
Category:	Lamps
Range Name:	Sunset
Product Type:	Vintage Decorative
Product Body Finish:	Amber
Market Segment:	Commercial indoor, Residential indoor, Vintage Decorative
Finish:	Amber
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	176
Product Width (mm):	125
Product Weight (g):	92
Material:	Glass
Base Term:	Bayonet cap
Bulb Base:	B22
Construction:	Glass shell, filament strip
Globe Finish:	Clear
Globe Type:	Globe 125
Bulb Fixing:	Pendant, Chandelier, Wall

Bulb or Luminaire Shape:	Round
Placement / Application:	Indoor, General Lighting

Electrical Data

Power (W):	2.5
Power Consumption (W) :	2.5
Power Factor:	0.5
Wattage equivalent (W):	40
Amperage (mA):	41
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	170
Luminous efficacy (lm/W):	68
Correlated Colour Temperature (CCT) (K):	1800
Colour Temperature:	1800K - Ultra Warm
Colour Temperature Name:	Ultra Warm
Beam Angle:	300
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Filament
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	188
Package Length (mm):	197
Package Width (mm):	126
Package Depth (mm):	126
Qty per euro pallet:	288