

**SUNSET GLOBE G95 B22 170LM 2.5W 1800K NON-DIMM 300 BEAM AMBER INTEGRAL**

ILGLOBB22N004



Create a relaxing ambience with an ultra-warm (1800K), energy-saving LED filament lamp. The Sunset range has a retro look with tinted amber glass and an eye-catching vintage design. Built using the latest LED filament technology to deliver an A+ energy rating and 93% energy savings compared to the incandescent lamp it replaces. Enjoy the classic aesthetic look but with an improved lifetime of 15,000 hours.

**Details**

<b>Quick Order Code:</b>	250577
<b>Barcode:</b>	5055788218388
<b>Category:</b>	Lamps
<b>Range Name:</b>	Sunset
<b>Product Type:</b>	Vintage Decorative
<b>Product Body Finish:</b>	Amber
<b>Market Segment:</b>	Commercial indoor, Residential indoor, Vintage Decorative
<b>Finish:</b>	Amber
<b>Warranty (Years):</b>	2
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Length (mm):</b>	138
<b>Product Width (mm):</b>	95
<b>Product Weight (g):</b>	61
<b>Material:</b>	Glass
<b>Base Term:</b>	Bayonet cap
<b>Bulb Base:</b>	B22
<b>Construction:</b>	Glass shell, filament strip
<b>Globe Finish:</b>	Clear
<b>Globe Type:</b>	Globe 95
<b>Bulb Fixing:</b>	Pendant, Chandelier, Wall
<b>Bulb or Luminaire Shape:</b>	Round
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power (W):</b>	2.5
<b>Power Consumption (W) :</b>	2.5
<b>Power Factor:</b>	0.5
<b>Wattage equivalent (W):</b>	40
<b>Amperage (mA):</b>	41
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	170
<b>Luminous efficacy (lm/W):</b>	68
<b>Correlated Colour Temperature (CCT) (K):</b>	1800
<b>Colour Temperature:</b>	1800K - Ultra Warm
<b>Colour Temperature Name:</b>	Ultra Warm
<b>Beam Angle:</b>	300
<b>Colour Rendering Index (CRI):</b>	80
<b>Frequency Range (Hz):</b>	50/60
<b>Instant on (Less than 1 second):</b>	Yes
<b>LED Type:</b>	Filament
<b>Lifetime (hours):</b>	15000
<b>Switching Cycles:</b>	7500

## Environment

<b>EN:</b>	EN-62560
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Package Weight (g):</b>	126
<b>Package Length (mm):</b>	159
<b>Package Width (mm):</b>	101
<b>Package Depth (mm):</b>	101
<b>Qty per euro pallet:</b>	360