SUNSET ST64 BULB B22 380LM 5W 1800K DIMMABLE 300 BEAM AMBER INTEGRAL

ILST64B22D004



Create a relaxing ambience with an ultra-warm (1800K), dimmable, energy-saving LED filament lamp. The Sunset range has a retro look with tinted amber glass and an eye-catching vintage design. Built using the latest LED filament technology to deliver an A+ energy rating and 93% energy savings compared to the incandescent lamp it replaces. Enjoy the classic aesthetic look but with an improved lifetime of 15,000 hours.

Details

Quick Order Code: Barcode: Category: Range Name: Product Type: Market Segment:	423864 5055788224150 Lamps Sunset Vintage Decorative Commercial indoor, Residential indoor, Vintage
Market Segment.	Decorative
Warranty (Years):	2
CE RoHS:	Yes
Physical Data	
Product Length (mm):	138
Product Width (mm):	64
Product Weight (g):	110
Material:	Aluminium, Glass
Base Term:	Bayonet cap
Bulb Base:	B22
Construction:	Glass shell, Filament strip, Aluminium base
Globe Finish:	Clear
Globe Type:	ST64
Bulb Fixing:	Pendant, Chandelier, Wall
Bulb or Luminaire Shape:	Oval
Placement / Application:	Indoor, Outdoor, General Lighting

Electrical Data

Power (W):

Power Consumption (W) :	5
Power Factor:	0.7
Wattage equivalent (W):	33
Amperage (mA):	29
Dimming:	Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-62560
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (Im):	380
Luminous efficacy (Im/W):	76
Correlated Colour Temperature (CCT) (K):	1800
Colour Temperature:	1800K - Ultra Warm
Colour Temperature Name:	Ultra Warm
Beam Angle:	290
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Type:	Filament chip
Lifetime (hours):	15000
Switching Cycles:	7500

Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	120
Package Length (mm):	72
Package Width (mm):	72
Package Depth (mm):	153
Qty per euro pallet:	900

Portal.integral-led.com