



## DATASHEET



### LDGL6

230V IP65 6W LED Stainless Steel Recessed Ground Light 3000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	LDGL6
DESCRIPTION	230V IP65 6W LED Stainless Steel Recessed Ground Light 3000K
NET WEIGHT (KG)	0.74
FINISH	Stainless Steel
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 129 Projection - 4 Recessed Depth - 70
CUT-OUT (MM)	Cut-out Diameter - 108 Cut-out with Sleeve - 114
CONSTRUCTION	Construction - 304 Stainless steel
CLASS	I
IP RATING	IP65
WATTAGE (W)	6
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	405
LUMENS LIGHT SOURCE ONLY (LM)	475
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	82.55
CIRCUIT WATTAGE (W)	5.8
CCT	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.033
DISPLACEMENT FACTOR	>0.9
SVM	0.08
PST-LM	0.39

BEAM ANGLE (DEGREES)	95
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
MAX. WEIGHT LOADING	800kg at 5mph
OPERATING TEMPERATURE	-25~35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	2
CABLE TYPE	3-core 1.00mm <sup>2</sup> H05RN-F
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270800388

Date Created: 26/04/2023 16:44

