## **X**nightsbridge

## **DATASHEET**



## 12DC25D

## **IP20 12V 25W DC Dimmable LED Driver - Constant Voltage**

www.mlaccessories.co.uk

DESCRIPTION  IP20 12V 25W DC Dimmable LED Driver - 0  NET WEIGHT (KG)  FINISH  White  Length - 128 Height - 30 Width - 52  CONSTRUCTION  Construction - ABS  CLASS  II  IP RATING  DISPLACEMENT FACTOR  SVM  0.37  PST-LM  0.37  LIFE SPAN (HRS)  DIMMABLE  Trailing-edge only*  INPUT VOLTAGE  SECONDARY VOLTAGE  DRIVER TYPE - Constant Volt MAX. OUTPUT CURRENT - 0 - 2080  OUTPUT CURRENT - 0 - 2080	Constant Voltage
FINISH  DIMENSIONS (MM)  CONSTRUCTION  DIP20  DISPLACEMENT FACTOR  POUR POUR POUR POUR POUR POUR POUR POUR	
DIMENSIONS (MM)         Length - 128	
DIMENSIONS (MM)         Height - 30 Width - 52           CONSTRUCTION         Construction - ABS           CLASS         II           IP RATING         IP20           DISPLACEMENT FACTOR         >0.9           SVM         0.37           PST-LM         0.37           LIFE SPAN (HRS)         50,000           DIMMABLE         Trailing-edge only*           INPUT VOLTAGE         230V 50Hz           SECONDARY VOLTAGE         12V           DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
CLASS II IP RATING IP20 DISPLACEMENT FACTOR >0.9 SVM 0.37 PST-LM 0.37 LIFE SPAN (HRS) 50,000 DIMMABLE Trailing-edge only* INPUT VOLTAGE 230V 50Hz SECONDARY VOLTAGE DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
IP RATING  DISPLACEMENT FACTOR  SVM  0.37  PST-LM  0.37  LIFE SPAN (HRS)  50,000  DIMMABLE  Trailing-edge only*  INPUT VOLTAGE  230V 50Hz  SECONDARY VOLTAGE  DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
DISPLACEMENT FACTOR  SVM  0.37  PST-LM  0.37  LIFE SPAN (HRS)  50,000  DIMMABLE  Trailing-edge only*  INPUT VOLTAGE  230V 50Hz  SECONDARY VOLTAGE  DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
SVM         0.37           PST-LM         0.37           LIFE SPAN (HRS)         50,000           DIMMABLE         Trailing-edge only*           INPUT VOLTAGE         230V 50Hz           SECONDARY VOLTAGE         12V           DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
PST-LM  0.37  LIFE SPAN (HRS)  50,000  DIMMABLE  Trailing-edge only*  INPUT VOLTAGE  230V 50Hz  SECONDARY VOLTAGE  12V  DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
LIFE SPAN (HRS)  DIMMABLE  Trailing-edge only*  INPUT VOLTAGE  SECONDARY VOLTAGE  12V  DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
DIMMABLE Trailing-edge only*  INPUT VOLTAGE 230V 50Hz  SECONDARY VOLTAGE 12V  DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
INPUT VOLTAGE  SECONDARY VOLTAGE  12V  DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
SECONDARY VOLTAGE  12V  DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
DRIVER TYPE - Constant Volt MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
MAX. OUTPUT - 25W OUTPUT VOLTAGE - 12V	
DRIVER  POWER FACTOR - 0.95  EFFICIENCY FULL LOAD - 8  ISOLATION - SELV  AMBIENT TEMPERATURE (Ta)7  CASE TEMPERATURE (Tc) - 7	0mA 34 20~50°C
WARRANTY 3year(s)	
MANUFACTURED IN ACCORDANCE WITH EN 61347, EN 62493	
ORIGIN OF MANUFACTURE China	
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	
<b>EAN</b> 5055832978961	

Date Created: 19/04/2023 15:46



