

KTC LED.Home 4W Candle

4W B22/E27/E14 Candle Lamp



Product Overview

Kosnic's Home range of LED products brings the energy saving capabilities of LED technology to the home. The KTC Candle range is both beautiful and functional giving a quality of light that creates inviting living spaces while offering lamps that deliver huge energy savings over filament lamps without compromising on brightness. The lamps can quickly replace filament products in domestic and hospitality lighting applications, and once in place rapid payback is achieved.

Features

- Metallic silver finishing to compliment chandeliers and decorative schemes.
- Popular B22, E27 and E14 caps.
- Save energy up to 85% compared with a filament lamp.
- High lumen output.
- Long life of 30,000h.
- Instant start.
- Negligible UV output.
- Mercury free.

Safety and Maintenance

- Switch off supply before installing or removing lamp. Allow to cool before handling.
- Do not use in totally enclosed fittings as this will reduce lamp life.
- Do not dispose of in household waste.
- Dispose of in appropriate section of local civic amenity site or recycling centre.

Specifications

Product Code	KTC04CND/B22-CLR-N30	KTC04CND/E14-CLR-N30	KTC04CND/E27-CLR-N30
Lamp Cap	B22	E14	E27
Lamp Shape	Candle	Candle	Candle
Nominal Power (W)	4	4	4
Voltage	220-240Vac 50-60Hz	220-240Vac 50-60Hz	220-240Vac 50-60Hz
Current (mA)	33	33	33
Nominal Luminous Flux (lm)	300	300	300
CCT (K)	3000K Warm White	3000K Warm White	3000K Warm White
Nominal Lifetime (h)	30000	30000	30000
Dimmable	No	No	No
Switching Cycles	50000	50000	50000
Warm-up time to 60% (S)	Instant full light	Instant full light	Instant full light
Length (mm)	115	117	115
Diameter (mm)	38	38	38
Mercury (mg)	0	0	0
Clean-up instructions	N/A	N/A	N/A
Retrofit	No	No	No
Equivalent Wattage (W)	28	28	28
Rated Power (W)	4.0	4.0	4.0
Rated Luminous Flux (lm)	300	300	300
Rated Lifetime (h)	30000	30000	30000
Power Factor	0.53	0.53	0.53
Rated Peak Candelas (cd)	6	6	6
Lumen Maintenance Factor at Nominal Lifetime	0.75	0.75	0.75
SDCM of CCT	<6	<6	<6
CRI	82	82	82
Start Time (s)	0.35	0.35	0.35
Ambient Temperature Range (°C)	-20 to 40	-20 to 40	-20 to 40


Energy Label

Manufacturer	Kosnic	Kosnic	Kosnic
Product Code	KTC04CND/B22-CLR-N30	KTC04CND/E14-CLR-N30	KTC04CND/E27-CLR-N30
Energy Class	A+	A+	A+
Energy Consumption (kWh/1000h)	4.0	4.0	4.0

Product Markings

Manufacturer	Kosnic	Kosnic	Kosnic
Product Code	KTC04CND/B22-CLR-N30	KTC04CND/E14-CLR-N30	KTC04CND/E27-CLR-N30
Voltage	220-240Vac 50-60Hz	220-240Vac 50-60Hz	220-240Vac 50-60Hz
Nominal Power (W)	4	4	4
Current (mA)	33	33	33
CE Mark	Yes	Yes	Yes
WEEE Mark	Yes	Yes	Yes
Batch Code	Yes	Yes	Yes

Dimensions



Photometric Information

3000K

