



- Surface Mount
- White Polycarbonate body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP65
- DDP (Deep Discharge Protection)
- Samsung LED's
- Kit of Legends for Ease of Stocking
- 25m Viewing Distance

A stylish and compact IP65 rated 3 Watt LED exit sign suitable for wall mounting. The unit is available as either a Switchable Maintained, Non-Maintained or a Switchable Maintained DALI Self-Test version. The fitting is not only more compact than the majority of LED exit signs, but offers an ingress protection of IP65 and a kit of legends for ease of installation and stocking.

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CE5S/3W/M3	Switchable Maintained IP65 Wall mounted Exit Sign
CE5S/3W/NM3	Non-Maintained IP65 Wall Mounted Exit Sign
CE5S/3W/DA	Switchable Maintained DALI Self-Test IP65 Wall Mounted Exit Sign

Technical Details:

	CE5S/3W/M3	CE5S/3W/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating	55mA $\lambda = 0.6$ Maintained	40mA $\lambda = 0.6$ Maintained
	25mA $\lambda = 0.6$ Non-maintained	16mA $\lambda = 0.48$ Non-maintained
Duration	3 Hours	
Recharge Period	12 Hours – Energy saving electronic charger	
Battery Size & Type	M3 = 6.4V 3.0Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	Dual Rate Charge 0-400mA	Dual Rate Charge 0-150mA
Ingress Protection Rating	IP65	
Light Source	8 pcs Samsung LED	
Possible Arrow Configurations	Arrow Up, Arrow Down, Arrow Left & Arrow Right	