



product details

41832 SSP

Product description: 41832 SSP
 Product code: 4050300335728
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300335728

| Applications | |
|------------------|-----|
| Dimmable | Yes |
| Burning position | any |

| Categorizations | |
|-----------------|--------------------------|
| SEG number | 8326750 |
| ILCOS | HMG5//UB-35-12-G53-111/4 |

| General Description | |
|-----------------------------|-----|
| Base (standard designation) | G53 |
| Mercury-free | Yes |

| Technical - Electrical Data | |
|-----------------------------|------|
| Nominal wattage (packaging) | 35 W |
| Construction wattage | 35 W |
| Nominal voltage | 12 V |

| Technical - Geometries | |
|------------------------|----------|
| Overall length | 60.00 mm |
| Contact spacing | 53 mm |
| Diameter | 111.0 mm |
| Length | 67.00 mm |

| Technical - Lifespan | |
|------------------------|--------|
| Nominal lamp life time | 2000 h |
| Rated lamp life time | 2000 h |

| Technical - Light Technical Data | |
|----------------------------------|----------|
| Rated color rendering index (Ra) | 100 |
| Luminous intensity | 30000 cd |
| Beam angle | 4 ° |
| Color temperature | 2800 K |
| Rated color temperature | 3000 K |
| Color rendering index Ra | 100 |
| Rated starting time | 0 s |

| Packaging units | | | | |
|-----------------|--------------------------------------|--------------------------------------|---------------------|------------------|
| Product code | Packaging type and content | Dimensions in h x w x l | Gross weight | Volume |
| 4050300335728 | Folding carton box contains 1 Piece | 61.000 mm x 60.000 mm x 82.000 mm | 91.667 g (0.000 g) | 0.838 Cubic dec. |
| 4050300335735 | Shipping carton box contains 6 Piece | 185.000 mm x 130.000 mm x 275.000 mm | 625.200 g (0.000 g) | 6.614 Cubic dec. |





product details

41832 SSP

Are you looking to highlight objects even in very bright surroundings? With HALOSPOT 111 from OSRAM that's not a problem. This halogen lamp with its large aluminum reflector provides optimum illumination and very little scattered light. The excellent focusing properties of this lamp enable extreme beam angles as tight as 4° to be achieved.

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Burner with axial filament for optimum distribution of light
- Drastically reduced thermal load in the luminaire thanks to an aluminium-coated reflector which emits most of the heat forwards
- Approved for use in open luminaires to IEC 60598-1
- Average life: 3,000 h
- Dimmable*
- Ra=100
- Color temperature: 35 W - 2,800 K; 50 W - 2,900 K; 75 W/100 W - 3,000 K
- Base: G53
- UV filter

For light distribution curves go to www.osram.com

* A buzzing tone may be heard when dimmed using certain dimmers. Recommendation: OSRAM HTI DALI 150/230-240 DIM with OSRAM DALI MCU