

Precise™ Standard MR16 & MR16 Start



Precise™ Standard MR16 and MR16 Start lamps are low voltage tungsten halogen reflector- mounted lamps popular for downlighting and accent lighting applications. The Cover Glass (closed) versions incorporate an integral clear lens to ensure that both bulb and reflector are protected from dust and dirt during installation and operation. The cover glass effectively eliminates UV- C radiation and greatly reduces UV- B radiation. The closed versions use the same reflectors as the open versions – and hence have the same dimensions, allowing users to interchange lamps at will.

- Small size
- Precise beam control
- High efficacy
- Excellent white light

The value engineered solution



Precise™ Standard MR16

W	D	Cd	△°	K	💡
12V – Dichroic Mirror – 50mm Open – Cap: GU5.3 – Rated Average Life: 3000 hours					
– UV Control					
20	M69/ BAB	500	30	3000	93419
35	M70/ FRA	3660	18	3000	93761
35	M81/ FMW	1620	30	3000	93423
50	M50/ EXZ	5920	18	3000	93760
50	M58/ EXN	2600	30	3000	93417
50	M80/ FNV	1190	55	3000	93421
12V – Dichroic Mirror – 50mm Closed – Cap: GU5.3 – Rated Average Life: 3000 hours					
– UV Control					
20	M269/ BAB/ CG	450	30	3000	93418
35	M270/ FRA/ CG	2950	18	3000	93763
35	M281/ FMW/ CG	1300	30	3000	93422
50	M250/ EXZ/ CG/	4750	18	3000	93762
50	M258/ EXN/ CG	2100	30	3000	93383
50	M280/ FNV/ CG	950	55	3000	93420

MR16 Start

W	D	Cd	△°	K	💡
12V – Bulb: clear, open, Cap: GU5.3 – Rated Average Life: 2000 hours					
20	M68/ ESX/ EC	3500	12	2900	38003
20	M69/ BAB/ EC	500	36	2900	38000
35	FRB/ EC	7500	12	3000	38004
35	M81/ FMW/ EC	925	36	3000	38001
50	M49/ EXT/ EC	9500	12	3000	38005
50	M50/ EXZ/ EC	2700	24	3000	39874
50	M58/ EXN/ EC	1500	36	3000	38002
50	M80/ FNV/ EC	630	55	3000	39881
12V – Bulb: clear, closed – Cap: GU5.3 – Rated Average Life: 2000 hours					
20	M268/ ESX/ CG/ EC	3150	12	2900	38012
20	M269/ BAB/ CG/ EC	450	36	2900	38006
35	FRB/ CG/ EC	6750	12	3000	38013
35	M281/ FMW/ CG/ EC	830	36	3000	38007
50	M249/ EXT/ CG/ EC	8550	12	3000	38014
50	M250/ EXZ/ CG/ EC	2700	24	3000	39611
50	M258/ EXN/ CG/ EC	1350	36	3000	38011
50	M280/ FNV/ CG/ EC	630	55	3000	39236