




LED

5
Year Warranty

IP21
Bathroom
Zone 3

Double
Insulated



Eterna
Everyday Lighting For Professionals

“DESIGNER STYLE” SHAVERLIGHT & MATCHING NON-SHAVER LUMINAIRE

Contemporary “designer style” alternative to standard functional products

- Vertical or horizontal mounting • Elegantly integrated push switch
- IP21 rated and insulated class 2 construction
- Available in chrome or white to compliment most bathroom decors

SHAVER LIGHTS

- Permanent power to shaver socket allowing use when not illuminated
- Dual voltage 110V and 240V shaver socket located under a slide to open cover maintains sleek appearance when not in use
- Please note: bathroom shaver lights are not suitable for toothbrush chargers



Both shaverlight and non-shaver versions are matching, creating an aesthetically pleasing appearance.



Code	Version	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
LEDOM5CR	Over Mirror	Chrome	5W	3000K	520 lm	25,000 hrs	IP21	1 / 10
LEDOM5WH		White						
LED5H6CR	Shaver Light	Chrome	6W					
LED5H6WH		White						

LED LAMP SPECIFICATIONS:	5W	6W
Luminaire lumens (with diffuser)	520 lm	520 lm
Lumens from chip (no diffuser)	595 lm	595 lm
Useful lumens	465 lm	465 lm
Rated Wattage	5W	6W
Rated luminous flux	465 lm	465 lm
Nominal life time of the lamp	25,000 hrs	25,000 hrs
Colour temperature	3000K	3000K
Number of switching cycles before premature lamp failure	12,500	12,500
Warm-up time up to 60% of the full light output	<1s	<1s
Dimmable	No	No
Nominal beam angle	120°	120°
Rated power	5W	6W
Rated lamp lifetime	25,000 hrs	25,000 hrs
Displacement factor		
Lumen maintenance factor at end of nominal life	70%	70%
Starting time	<0.5s	<0.5s
Colour rendering	≥80	≥80
Colour consistency	Within a six step Macadam ellipse	Within a six step Macadam ellipse
Rated peak intensity	149cd	149cd
Rated beam angle	120°	120°
Voltage / Frequency	240V~50Hz	240V~50Hz
Lumen efficacy	104 lm / W	86.6 lm / W
Class 2 double insulated Not suitable for accent lighting		