

Product selected: F58W/940

A new generation of triphosphor coated fluorescent tubes. Using T8 triphosphor tubes in place of T12 and T8 halophosphor tubes increases light levels and extends lamp life, up to 20000 hours when used with electronic control gear, improves colour rendering performance and reduces maintenance and energy costs.

Applications

- Industrial and commercial lighting (stores, offices, industrial areas, supermarkets)
- Special lengths in luminaires with non-standard dimensions, displays, furniture lighting, shops, bathroom luminaires


Features

- High light output; almost constant lumen maintenance throughout life
- High colour rendering (Ra85/Class 1B)
- Consumes 10% less energy than comparable 38mm fluorescent tubes
- Excellent performance (lm/W) and increased luminaire efficiency (5 to 10%)
- Operates on conventional and electronic ballast

Product Attributes

Item description	F58W/940
Nominal wattage (W)	58
Rated Wattage (W) HF	50.0
Bulb finish / Light colour	Coolwhite Deluxe
Cap	G13
Maximum Lamp length L [mm]	1514.2
Diameter D [mm]	26
Mercury content per lamp [mg]	3.3
Colour rendering Index - CRI (class / %)	/91
Colour temperature (K)	4000
Nominal luminous flux at 25°C (lm)	4600
Nominal luminous flux at 35°C (lm)	-
Lumen maintenance min. 2000 h (50 Hz)	0.96
Lumen maintenance min. 4000 h (50 Hz)	0.94
Lumen maintenance min. 6000 h (50 Hz)	0.92
Lumen maintenance min. 8000 h (50 Hz)	0.91
Lumen maintenance min. 12000 h (50 Hz)	0.9
Lumen maintenance min. 16000 h (50 Hz)	0.89
Lumen maintenance min. 20000 h (50 Hz)	0.87
Lumen maintenance min. 2000 h (HF preheat)	n.a.
Lumen maintenance min. 4000 h (HF preheat)	n.a.
Lumen maintenance min. 6000 h (HF preheat)	n.a.
Lumen maintenance min. 8000 h (HF preheat)	n.a.
Lumen maintenance min. 12000 h (HF preheat)	n.a.
Lumen maintenance min. 16000 h (HF preheat)	n.a.
Lumen maintenance min. 20000 h (HF preheat)	n.a.
Ambient temperature for max. lumen flux (°C)	25
Nominal average life (h)	20000
Survival factor 2000 h (50 Hz)	0.99
Survival factor 4000 h (50 Hz)	0.98
Survival factor 6000 h (50 Hz)	0.96
Survival factor 8000 h (50 Hz)	0.93
Survival factor 12000 h (50 Hz)	0.91
Survival factor 20000 h (50 Hz)	n.a.
Survival factor 2000 h (HF)	n.a.
Survival factor 4000 h (HF)	n.a.
Survival factor 6000 h (HF)	n.a.

Product Image

Cap (image)
G13

 T8 max. 25,78
 T12 max. 36,52

Survival factor 8000 h (HF)	n.a.
Survival factor 12000 h (HF)	n.a.
Survival factor 16000 h (HF)	n.a.
Survival factor 20000 h (HF)	n.a.
Packing Quantity	25
EAN Code	5410288015828
Ordering Code	0001582

Fixture rating

