

LOW VOLTAGE HALOGEN DICHROIC - STANDARD



Halogen dichroic lamps giving high output illumination, precision distribution and long life.

- UV stop front cover glass
- Long life
- 35mm (MR11) or 50mm (MR16)
- 1A Colour Rendering Index
- Dimmable
- Coolbeam lamp - must be used in open or well ventilated fittings which can dissipate heat emitted from the back of the lamp

* See page 20 for LED low energy versions

* See page 36 for energy saving Halogen


59

Order Code	Watts (W)	Volts (V)	Beam Angle	UK Ref	Cap	Colour Temp (°K)	*Candelas	Average Rated Life (hrs)	Order Qty
35mm (MR11) Single Carton#									
LV3520MS	20	12	20°	M251	GU4	2700	200	4000	20
LV3520MF	20	12	38°	M221	GU4	2700	200	4000	20
LV3535MS	35	12	20°	M266	GU4	2800	450	4000	20
LV3535MF	35	12	38°	M223	GU4	2800	450	4000	20
50mm (MR16) Single Carton#									
LV20M	20	12	38°	M269	GU5.3	3100	700	5000	20
LV35M	35	12	38°	M281	GU5.3	3100	1500	5000	20
LV50MS	50	12	24°	M250	GU5.3	3100	4000	5000	20
LV50MF	50	12	38°	M258	GU5.3	3100	2000	5000	20
LV50N	50	12	10°	M249	GU5.3	3100	10000	5000	20
LV50V	50	12	60°	M280	GU5.3	3100	1050	5000	20
50mm (MR16) Aluminium Coated Single Carton									
LV20MACOAT	20	12	38°	M269	GU5.3	3100	700	5000	20
LV35MACOAT	35	12	38°	M281	GU5.3	3100	1500	5000	20
LV50MACOAT	50	12	38°	M258	GU5.3	3100	2000	5000	20
50mm (MR16) Twin Blister Pack#									
BPLV20MF-2BL	20	12	38°	M269	GU5.3	3100	700	5000	20
BPLV50MF-2BL	50	12	38°	M258	GU5.3	3100	2000	5000	20

* Lumen values = luminous intensity @ peak (in candelas)

Indicates Cool Beam

DIMENSIONS



GU4 cap



GU5.3/GX5.3 cap

Lamp Type	Dia (mm)	H (mm)
35mm (MR11)	35	35
50mm (MR16)	51	49



Low Voltage