



product details

41900 SP

Product description: 41900 SP
 Product code: 4050300003962
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300003962

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
SEG number	8326702
ILCOS	HMG5//UB-20-12-GY4-48/8

General Description	
Base (standard designation)	GY4
Mercury-free	Yes

Technical - Electrical Data	
Nominal wattage (packaging)	20 W
Construction wattage	20 W
Nominal voltage	12 V

Technical - Geometries	
Overall length	36.00 mm
Contact spacing	4 mm
Diameter	48.0 mm
Length	38.00 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Luminous intensity	3100 cd
Beam angle	8 °
Color temperature	2900 K
Color rendering index Ra	100
Rated starting time	0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300003962	Folding carton box contains 1 Piece	44.000 mm x 44.000 mm x 57.000 mm	20.700 g (0.000 g)	0.110 Cubic dec.
4050300217536	Shipping carton box contains 10 Piece	96.000 mm x 69.000 mm x 231.000 mm	253.000 g (0.000 g)	1.530 Cubic dec.



product details

41900 SP

Presenting things in a better light. Thanks to their excellent spotlighting and extremely high luminous intensity HALOSPOT 48 from OSRAM are real professionals when it comes to presenting rooms and objects in their best light. The faceted reflector ensures the light is evenly distributed. With HALOSPOT lamps there is no need to worry about heat building up in suspended ceilings because the aluminum reflector ensures that most of the heat is emitted forwards.

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Excellent distribution of light thanks to faceted reflector
- Drastically reduced thermal load in the luminaire thanks to an aluminium-coated reflector which emits most of the heat forwards
- Approved for use in open luminaires to IEC 60598-1
- Average life: AR48 20 W 24 V - 1,000 h; AR48 20 W 12 V - 2,000 h
- Dimmable*
- Ra=100
- Color temperature: 2,800 K
- Base: BA15d, GY4
- UV filter

For light distribution curves go to www.osram.com

*A buzzing tone may be heard when dimmed using certain dimmers. Recommendation: OSRAM HTI DALI 150/230-240 DIM with OSRAM DALI MCU