



product details

64432 S

Product description: 64432 S
 Product code: 4050300017426
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300017426

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
SEG number	8326538
ILCOS	HSGST/C/UB-35-12-GY6,35-12/30

General Description	
Base (standard designation)	GY6.35
Filament setting	Axial
Mercury-free	Yes
Rated lamp mercury content	0.0 mg

Technical - Electrical Data	
Nominal wattage (packaging)	35 W
Construction wattage	35 W
Nominal voltage	12 V
Rated number of switching cycles	1000000
Rated power factor λ	1.00

Technical - Geometries	
Overall length	44.00 mm
Contact spacing	6.35 mm
Diameter	12 mm
Length	44.00 mm
Light center length (LCL)	30 mm

Technical - Lifespan	
Nominal lamp life time	4000 h
Rated lamp life time	4000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	100
Luminous flux	580 lm
Nominal luminous flux	580 lm
Rated luminous flux	580 lm
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2900 K
Rated color temperature	2900 K
Color rendering index Ra	100
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s



product details

64432 S

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300017426	Folding carton box contains 1 Piece	25.000 mm x 20.000 mm x 70.000 mm	5.000 g (0.000 g)	0.040 Cubic dec.
4050300942179	Shipping carton box contains 40 Piece	121.000 mm x 107.000 mm x 144.000 mm	208.000 g (0.000 g)	1.864 Cubic dec.

Paving the way for new luminaire designs: HALOSTAR STARLITE from OSRAM. With freeburning halogen lamps and their bright pools of light it is possible to provide accent lighting for entire rooms. Entrance halls and reception rooms appear in a new vibrant light. They may even be transformed by sculptures in light. Their long average life of 4,000 hours is truly impressive.

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires to IEC 60598-1
- Axial filament for optimum directional light
- Special pins for corrosion protection
- Average life span: 4,000 h
- Dimmable
- R_a =100
- Color temperature: 5 W/10 W (6 V) - 2,700 K; 10 W/20 W - 2,800 K; 35 W - 2,900 K; 50 W/75 W/90 W - 3,000 K
- Base: G4, GY6.35
- UV filter